

10/509857

DT09 Rec'd PCT/PTO 0 1 OCT 2004

Claims**ART 34 AMDT**What is claimed is:

1. (Deleted)
2. (Amended) A equipment for spread spectrum communication comprising:

a toggle detecting unit configured for detecting a candidate of a toggle point existing in a carrier of a received signal by correlating between the carrier of the received signal and a pre-held expected signal, and the pre-held expected signal is a signal including a waveform of the toggle point which is expected to be in the carrier of the received signal and is a signal having length corresponding to 2 chip-times of a spread code or is a signal having shorter length than it; and

a demodulating unit configured for demodulating the received signal by multiplying the received signal by the spread code which is shifted according to a shift amount calculated based on a result of the detected candidate.
3. (Amended) The equipment as claimed in claim 2, wherein said toggle detecting unit is configured for outputting a toggle signal as a result of detecting of the candidate of the toggle point, a candidate of the shift amount which is to be provided to the spread code is calculated based on cross-correlation of the toggle signal and absolute value of differentiated value of the spread code, said demodulating unit is configured for

ART 34 AMDT

demodulating the received signal by shifting the spread code with respect to the each candidate of the shift amount, and effectiveness of a carrier spectrum of the received signal demodulated in the demodulating unit is inspected.

4. (Amended) The equipment as claimed in claim 3, wherein the candidate of the shift amount which is to be provided to the spread code is calculated by correlating between Fourier transformed value of the toggle signal and Fourier transformed value of the absolute value of differentiated value of the spread code.

5. (Deleted)

6. (Amended) A high-speed synchronization establishing method for spread spectrum communication comprising:

the first step of detecting a candidate of a toggle point existing in a carrier of a received signal,

the second step of calculating a shift amount based on a result of the detected candidate, and

the third step of demodulating the received signal by multiplying the received signal by a spread code shifted according to the calculated shift amount;

an expected signal which includes an waveform of the toggle point expected to be in the carrier of the received signal and has length corresponding to 2 chip-times of the spread code or has shorter length than it is prepared previously; and

the candidate of the toggle point is detected by correlating

ART 34 AMDT

between said expected signal and the carrier of the received signal in said the first step.

7. The high-speed synchronization establishing method for spread spectrum communication as claimed in claim 6, wherein a toggle signal as a result of detecting of the candidate of the toggle point is outputted in said the first step,

a candidate of the shift amount which is to be provided to the spread code is calculated based on cross-correlation of the toggle signal and absolute value of differentiated value of the spread code in said the second step,

the received signal is demodulated with respect to the each candidate of the shift amount and effectiveness of a carrier spectrum of the demodulated received signal is inspected in said the third step.

8. The high-speed synchronization establishing method for spread spectrum communication as claimed in claim 7, wherein Fourier transformed value of the toggle signal and Fourier transformed value of the absolute value of differentiated value of the spread code are correlated when the candidate of the shift amount which is to be provided to the spread code is calculated in said the second step.